The MC860 Colour and Mono Multifunction Product

		MC860dn	MC860cdtn	MC860cdxn		
Order number		01236201	01236301	01236401		
Speed & throughput	Print speed	A4: 26ppm colour, 34ppm mono; A3: 15ppm colour, 17ppm mono				
	Time to first print	10 seconds colour, 9.5 seconds mono				
	Warm up time	90 seconds or less from power on				
	Processor speed	PowerPC750 500MHz				
Scan		Resolution: 600 x 600dpi; Speed: Up to 26spm colour, 34spm mono; Colour depth: Output 24 bit (8 bit x 3 RGB); Document input: Upto 50 sheet RADF; Contrast: 7 Levels; Format: PDF, TIFF, JPEG, XPS; Addressbook: LDAP & internal address book; Scan to: Folder (CIFS), E-Mail, FTP, HTTP, USB Memory				
Сору		First copy out: 14.5 seconds colour, 13 seconds mono; Speed: 26cpm colour, 34cpm mono; Resolution: 600dpi; Reduction / Enlargement: 25-400 %; Maximum copies: 999				
Fax		Connectivity: RJ11 x 2 (Line/Tel) PSTN, PBX; Speed: ITU-T G3 (Super G3) 33.6kbps; Fast dialing: 500 speed dials; Groups: 32; Broadcast: up to 530; Page memory: 16MB (approx 1,000 pages)				
Operator panel	LCD Touch-screen	14.5cm back-lit				
	Key pad	12 numeric, 4 main function buttons, Color & Mono Start, Setup, Job Programs, Reports, Reset, Help, Power Save, Interrupt Key, Fax Job View/Cancel & Stop Key				
Print quality	Resolution	Pro	Q 2400 Multi-level technology 1200 x 600 dpi	i		
	Enhancements	Auto Colour Balance, Photo Enhance via Driver (Windows only)				
Typefaces	Printer fonts	Scalable: 86 PCL fonts & 136 PostScript fonts, PCL Bitmap fonts, OCR-A/B, USPS ZIP Barcode				
Compatibility	Printer languages	PCL 5c, PCL 6 (Windows), PostScript (Windows/Mac)				
	Connectivity	Hi-Speed USB, 10/100-TX Ethernet, Parallel Port				
	OS Compatibility ¹	Windows 2000 / XP Home / XP Professional / XP Professional x64 / Server 2003 / Server 2003 x64 / Vista x64 / Server 2008 / Server 2008 x64; Mac OS X 10.3.0 to 10.5.5				
	Network & protocols	10Base-T/100Base-TX Ethernet Card with internal Web Server for printer and network card set-up and management. Includes POP3/APOP and SMTP Mail client for submission of print jobs and for alerts. All major network protocols supported - TCP/IP:- ARP, RARP, IPv4/v6, CMPv4/v6, TCP, UDP, LPR, FTP, TELNET, HTTP(IPP), BOOTP, DHCP, SNMPv1/v3, DNS, DDNS, UPnP, Bonjour, WINS, SSL/TLS, SMTP, POP3, SNTP, WSDPrint, JetDirect protocols, NetBIOSoverTCP, Kerberos. NetWare 3.x, 4.x, 5.x & 6 with full NDS and NDPS support:- PServer, RPrinter, NDPS supported via dedicated OKI NDPS Gateway. Ethertalk:- ELAP, AARP, DDP, AEP, NBP, ZIP, RTMP, ATP, PAP. NetBEUI:- SMB, NetBIOS. Other:-EAP				
	Advanced networking	IPv6, 802.1x authentication, SNMPv3, SSL3/TLS HTTPS encryption, Secure Erase, Data Encryption,				
	and security	MAC filtering, IP filtering, Secure Print				
Utility Suite ¹		Color Correct, OKI LPR ² , PrintSuperVision.net ² , Swatch Utility, Template Manager 3.0 ² , Web Driver Installer ² , WebPrint ² , Print Control Server ² , Print Control Client, Print Control Report Tool ² , Storage Device Manager ² , Gamma Utility, Profile Assistant, PDF Direct Utility, Configuration Tool, Scansoft Omnipage SE 4.0, Scansoft Paperport SE 11				
Memory	RAM	Standard: 512MB (2 x 256MB); Maximum: 768MB (1 x 256MB, 1 x 512MB)				
	Hard Disk Drive	40GB Standard				
Paper handling	Paper capacity	Tray 1: 300 sheets of 80gsm; Multi-purpose tray: 100 sheets of 80gsm; RADF: 50 sheets of 80gsm				
	Paper capacity optional 2nd tray + tall cabinet (standard on MC860cdtn)	530 sheets of 80gsm				
	Paper capacity optional 2nd/3rd tray + short cabinet (standard on MC860cdxn)	1060 sheets of 80gsm				
	Max paper capacity	400 sheets of 80gsm	930 sheets of 80gsm	1460 sheets of 80gsm		
	Paper sizes	Tray 1: A3, B4, A4, A5, B5, A6; Tray 2/3: A3, B4, A4, A5, B5; Multi-purpose tray: A3, B4, A4, B5, A5, A6. Envelopes (Com10, DL, C4, C5), Labels (Avery 7162, 7664, 7666), Transparencies. Support Custom size: Width 64-297mm Length 105-1200mm; RADF: A3, A4, A5, B4, B5. Supports custom size: Width 148,5-297mm Length: 182-431.8mm				
	Paper weight	Tray 1: 64 to 120gsm; Tray 2/3: 64 to 176gsm; Multi-purpose tray: 64 to 200gsm; RADF: 42 to 128gsm; Duplex: 64 to 105gsm				
	Paper output	Iray 1: 64 to 120gsm; Iray 2/3: 64 to 1/6gsm; Multi-purpose tray: 64 to 200gsm; KADF: 42 to 128gsm; Duplex: 64 to 105gsm 250 sheets face down. 100 sheets face up				
Operating conditions	Temperature/Humidity	250 sheets face down, 100 sheets face up -10°C to 32°C (17°C to 27°C recommended) / 20% to 80% RH (50% to 70% RH recommended)				
operating conditions		-10°C to 32°C (1/°C to 2/°C recommended) / 20% to 80% RH (50% to 70% RH recommended) -10°C to 43°C / 10% to 90% RH				
Operating conditions	Storage	,				
, ,	Storage Power supply	Cinala	· · ·	2%		
Power requirements	Power supply		phase 220-240VAC, frequency 50/60Hz +/-			
Power requirements	0	Typical 700V	phase 220–240VAC, frequency 50/60Hz +/- N, Peak 1300W, Idle 160W (average), Power Sa	ave < 25W		
Power requirements Noise level	Power supply	Typical 700V Operating: 54dB(phase 220–240VAC, frequency 50/60Hz +/- N, Peak 1300W, Idle 160W (average), Power Sa A) or less, Standby: 37dB(A) or less, Power sa	ave < 25W re: Background		
Power requirements Noise level Dimensions (HxWxD)	Power supply	Typical 700V Operating: 54dB(669 x 565 x 658mm	phase 220–240VAC, frequency 50/60Hz +/- W, Peak 1300W, Idle 160W (average), Power Sa A) or less, Standby: 37dB(A) or less, Power sav 1130 x 84	ave < 25W re: Background 5 x 766mm		
Power requirements Noise level Dimensions (HxWxD) Weight ³	Power supply Power consumption	Typical 7000 Operating: 54dB(669 x 565 x 658mm 68kg approx	phase 220–240VAC, frequency 50/60Hz +/- W, Peak 1300W, Idle 160W (average), Power Sa A) or less, Standby: 37dB(A) or less, Power sav 1130 x 84 95kg approx	ave < 25W re: Background 5 x 766mm 100kg approx		
Power requirements Noise level Dimensions (HxWxD) Weight ³ Duty cycle	Power supply	Typical 7000 Operating: 54dB(669 x 565 x 658mm 68kg approx	phase 220–240VAC, frequency 50/60Hz +/- W, Peak 1300W, Idle 160W (average), Power Sav A) or less, Standby: 37dB(A) or less, Power sav 1130 x 84 95kg approx 50,000 pages/month; Average: 10,000 pages	ave < 25W re: Background 5 x 766mm 100kg approx		
Power requirements Noise level Dimensions (HxWxD) Weight ³ Duty cycle Warranty	Power supply Power consumption Printer duty	Typical 7000 Operating: 54dB(669 x 565 x 658mm 68kg approx Maximum:	phase 220–240VAC, frequency 50/60Hz +/- W, Peak 1300W, Idle 160W (average), Power Sa A) or less, Standby: 37dB(A) or less, Power sav 1130 x 84 95kg approx	ave < 25W re: Background 5 x 766mm 100kg approx s/month		
Power requirements Noise level Dimensions (HxWxD) Weight ³ Duty cycle	Power supply Power consumption	Typical 7000 Operating: 54dB(669 x 565 x 658mm 68kg approx Maximum: o (44020403)	phase 220–240VAC, frequency 50/60Hz +/- W, Peak 1300W, Idle 160W (average), Power Sav A) or less, Standby: 37dB(A) or less, Power sav 1130 x 84 95kg approx 50,000 pages/month; Average: 10,000 pages	ave < 25W re: Background 5 x 766mm 100kg approx		

Standard o Optional (Order number)
 Check local OKI Printing Solutions website for latest driver releases & OS Compatibility

² Windows only ³ Includes all consumables

Specification subject to change without notice. All trademarks acknowledged.

Consumables

For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI Printing Solutions toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

Description	Life* (pages)	Order Numbers	
Toners	9,500 mono, 10,000 colour	Cyan: 44059211 Yellow: 44059209	Magenta: 44059210 Black: 44059212
Image drum	20,000	Cyan: 44064011 Yellow: 44064009	Magenta: 44064010 Black: 44064012
Transfer belt	80,000	43449705	
Fuser unit	100,000	43529405	

*All toners: A4 pages @ ISO/IEC 19798, Printer shipped with 1,250 pages @ 5%. All Drums: A4 pages average life.

OKI SYSTEMS (UK) LTD. 550 Dundee Road, Slough Berkshire, SL1 4LE United Kingdom T+44(0) 1753 819819 F+44(0) 1753 819899 WWW.OKIPRINTINGSOLUTIONS.CO.UK







MC860 Specifications





The ultra compact A4 and A3 MFP

The MC860 is the perfect workgroup 4-in-1 MFP device for A4 and A3 output. With print speeds of up to 34ppm A4 and 17ppm A3 the ultra compact MC860 increases efficiency for workgroups or small businesses.

Easily integrated in any network, the MC860 provides fast easy access to a solution for all mono and colour print or copy needs. It can send and receive faxes with a few keystrokes and scans documents to network, computer, email and even direct to USB.

The MC860 includes a unique set of software designed to help users get the most of their product and investment. These advanced utilities come as standard in the box and deliver increased printing power and management control. For a complete list of utilities refer to the product specification table overleaf.

MC860dn duplex, network 400 sheets in total

MC860cdtn duplex, network, 2nd tray + tall cabinet 930 sheets in total



MC860cdxn duplex, network, 2nd/3rd tray + short cabinet 1460 sheets in total